



Overview:

The CLP range is available in various diameters, 600mm, 950mm and 1200mm, with a range of fixing options. All options are 100mm wide and 100mm deep.

LED board spacing ensures a seamless halo effect luminaire.

Bespoke diameters available upon request.

Range:

Powered by Tridonic or Harvard light engines.

Suspended luminaires provided with 2 metre wire suspensions as standard.

Dimming and Emergency options.

Two colour temps: 3000K & 4000K

Two optic options: OP (Satine) & MP (UGR Optimised micro prism)

Mounting:

Surface (SUR)

Pendant (PEN)

Suspended Direct/Indirect (SUD)

Construction:

Extruded aluminium

Controls:

Electronic	- ELE
DSI	- DSI
DALI	- DALI

Efficiency:

Optical efficiency (DLOR)	MP - 76%
	OP - 68%

Model Ref / Wattage / Lumen package / Colour temp

CLP.600.100.X.250mA.OP.XX	13.2W	2420lm	4000K
CLP.600.100.X.250mA.MP.XX	13.2W	2420lm	4000K
CLP.600.100.X.500mA.OP.XX	33.0W	4950lm	4000K
CLP.600.100.X.500mA.MP.XX	33.0W	4950lm	4000K
CLP.950.100.X.250mA.OP.XX	21.6W	3960lm	4000K
CLP.950.100.X.250mA.MP.XX	21.6W	3960lm	4000K
CLP.950.100.X.500mA.OP.XX	54.0W	8100lm	4000K
CLP.950.100.X.500mA.MP.XX	54.0W	8100lm	4000K
CLP.1200.100.X.250mA.OP.XX	28.8W	5280lm	4000K
CLP.1200.100.X.250mA.MP.XX	28.8W	5280lm	4000K
CLP.1200.100.X.500mA.OP.XX	72.0W	10800lm	4000K
CLP.1200.100.X.500mA.MP.XX	72.0W	10800lm	4000K

X Denotes operating driver - ELEC / DSI / DALI

XX Denotes mounting - SUR / PEN / SUD

* Above data quoted is for Tridonic LLE Advanced board, at 250mA & 500mA, direct light only. Various outputs inbetween those quoted above are available, as well as indirect lighting data upon request. Wattage quoted does not include any losses from the driver.

* Data for 3000K is available upon request.