



### Overview:

The DPR-PF range is a sealed modular LED luminaire suitable for kitchens and clean room environments, rated ingress protection or IP54, manufactured from steel, with a RAL 9010 20% finish.

### Range:

Powered by Tridonic light engines.  
 Provided with a polar frost high efficiency optic.  
 Modules available in two sizes, 600mm x 600mm, 1200mm x 300mm, both versions are 80mm deep.  
 Dimming options  
 Emergency options  
 Two colour temps: 3000K & 4000K

### Mounting:

Recessed

### Construction:

Steel fabrication

### Controls:

Electronic	- ELE
DALI	- DALI
DSI	- DSI
Emergency 3hr	- EM
Emergency 3hr EPFRO	- EPF

### Efficiency:

Optical efficiency (DLOR)	68%
---------------------------	-----

### Model Ref / Wattage / Lumen package / Colour temp

DPR-PF.6.6.QG1.X.4K.350mA	37.6W	5280lm	4000K
DPR-PF.6.6.QG1.X.4K.500mA	56.2W	7280lm	4000K
DPR-PF.12.3.QG1.X.4K.350mA	37.6W	5280lm	4000K
DPR-PF.12.3.QG1.X.4K.500mA	56.2W	7280lm	4000K

\* Above data quoted if for Tridonic QLE G1 LED light engines

\*\* IP rating can be improved upon request

\*\*\* X denotes operating driver - ELE / DALI / DSI

