



### Overview:

The PEDLED.94 range is a LED pendant with polycarbonate Lexalite reflector refractor.

### Range:

Powered by Philips DLM Flex light engine.  
Supplied with an adjustable 2m suspension kit.  
Available with a conical lens and gear housing colour combinations.

Dimming options.

Two colour temps: 3000K & 4000K

### Mounting:

Suspended - 420mm high, Weight 3.1kg

### Construction:

Polycarbonate Lexalite Reflexor refractor

### Controls:

Electronic	- Standard
touchDIM, DALI	- T+DALI

### Efficiency:

Optical efficiency (DLOR)	94%
---------------------------	-----

### Model Ref / Wattage / Lumen package / Colour temp

Model Ref	Wattage	Lumen package	Colour temp
PEDLED.94.1100.30/X\	11.0W	1005lm	3000K
PEDLED.94.1100.40/X\	11.2W	1092lm	4000K
PEDLED.94.2000.30/X\	20.6W	1969lm	3000K
PEDLED.94.2000.40/X\	20.6W	2139lm	4000K
PEDLED.94.3000.30/X\	30.1W	2997lm	3000K
PEDLED.94.3000.40/X\	30.0W	3250lm	4000K
PEDLED.94.5000.30/X\	48.5W	4700lm	3000K
PEDLED.94.5000.40/X\	48.6W	5099lm	4000K

\*Nuventix active cooling