



Overview:

Mini pinhole downlight available with a wide range of features including fixed or tiltable. Bodies with a variety of baffle, body and lens options.

Range:

Tridonic light engine recessed downlight.
Fitted with an integral IP44 protective lens.
Black, white and gold baffles available, other colours available upon request.
IP54 ribbed glass, honeycomb and lens options.
Dimming options
Emergency options
Three colour temps: 2700K, 3000K & 4000K

Mounting:

Recessed - 100mm high, weight 0.3kg
Ceiling depth - max. 26mm
Fixed and tiltable
Diameter - 76mm, Cut-out - 65mm

Construction:

Bezel die-cast from pure aluminium

Controls:

Electronic	- Standard
SwitchDIM, DALI, DSI	- ECO
Emergency 3hr	- EM
Emergency 3hr self test	- EMS
Emergency 3hr DALI	- EMD

Efficiency:

Optical efficiency (DLOR)	70%
---------------------------	-----

Model Ref / Wattage / Luminaire Output / Colour temp

Model Ref	Wattage	Luminaire Output	Colour temp
RLED1.175.001	8.5W	355lm	2700K
RLED1.175.002	8.5W	431lm	3000K
RLED1.175.003	8.5W	450lm	4000K
RLED1.175.004	10.5W	462lm	2700K
RLED1.175.005	10.5W	559lm	3000K
RLED1.175.006	10.5W	583lm	4000K