



Overview:

The RLED1.96 range is a LED downlight, less than 100mm in height, with multi-faceted, satine or specular reflector.

Range:

Powered by Tridonic SLE light engine.
Die-cast twist and lock bezel allows for a range of interchangeable accessories.
Compatible with the PI200 Plaster in kit.
Dimming options.
Supplied with medium beam reflector as standard, with narrow and wide beam options available.
Two colour options: 3000K and 4000K

Mounting:

Recessed - 99mm high, Weight 0.5kg
Ceiling depth - 25mm max
Diameter - 130mm

Construction:

Die-cast Aluminium

Controls:

Electronic switchDIM, DALI, DSI - Standard
- ECO
Plaster in Kit - PI200

Efficiency:

Optical efficiency (DLOR) 93%

Model Ref / Wattage / Luminaire Output / Colour temp

Model Ref	Wattage	Luminaire Output	Colour temp
RLED1.96.001	8.0W	1020lm	3000K
RLED1.96.002	8.0W	1055lm	4000K
RLED1.96.003	13.8W	1725lm	3000K
RLED1.96.004	13.8W	1787lm	4000K
RLED1.96.005	19.2W	2363lm	3000K
RLED1.96.006	19.2W	2442lm	4000K
RLED1.96.007	27.8W	3146lm	3000K
RLED1.96.008	27.8W	3252lm	4000K