



Overview:

The RLED2.103 range is a LED downlight with Philips DLM Flex module, fitted with a satin etched, multi faceted or specular reflector.

Range:

Philips DLM Flex light engine recessed downlight.
Fitted with a discreet low profile bezel
Dimming options
Emergency options
Two colour temps: 3000K & 4000K

Mounting:

Recessed - 163mm high, weight 1.0kg
Ceiling depth -min. 10mm - max. 30mm
Diameter - 189mm

Construction:

Bezel die-cast from pure aluminium

Controls:

Electronic	- Standard
touchDIM, DALI	- ECO
Emergency 3hr	- EM
Emergency 3hr self test	- EMS
Emergency 3hr EMPRO	- EMP

Efficiency:

Optical efficiency (DLOR)	87%
---------------------------	-----

Model Ref / Wattage / Luminaire Output / Colour temp

Model Ref	Wattage	Luminaire Output	Colour temp
RLED2.103.1100.40	15.1W	1156lm	4000K
RLED2.103.2000.40	25.2W	1938lm	4000K
RLED2.103.3000.40	24.8W	2537lm	4000K
RLED2.103.5000.40	46.4W	3792lm	4000K
RLED2.103.1100.30	15.1W	1058lm	3000K
RLED2.103.2000.30	25.1W	1771lm	3000K
RLED2.103.3000.30	34.7W	2537lm	3000K
RLED2.103.5000.30	46.3W	3474lm	3000K

* 5 year warranty