



Overview:

The RLED2.110 range is a LED downlight with Tridonic DLE module, fitted with a satin etched, multi faceted or specular reflector.

Range:

Tridonic DLE light engine recessed downlight.

Fitted with a twist and lock bezel.

Dimming options.

Emergency options.

Two colour temps: 3000K & 4000K, plus Tuneable White

Mounting:

Recessed - 134mm high, weight 1.8kg

Ceiling depth -min. 5mm - max. 40mm

Diameter - 195mm

Construction:

Bezel die-cast from pure aluminium

Controls:

Electronic	- Standard
touchDIM, DALI	- ECO
Emergency 3hr	- EM
Emergency 3hr self test	- EMS
Emergency 3hr EMPRO	- EMP

Efficiency:

Optical efficiency (DLOR) 87%

Model Ref / Wattage / Luminaire Output / Colour temp

RLED2.110.2001	11.1W	1139lm	3000K
RLED2.110.2002	19.4W	1881lm	3000K
RLED2.110.2003	9.9W	1052lm	4000K
RLED2.110.2004	18.2W	1858lm	4000K
RLED2.110.3002	26.4W	2677lm	3000K
RLED2.110.3004	26.4W	2820lm	4000K
RLED2.110.2000.TUNE	17.7W	1740lm	Tuneable

* 5 year warranty