

### Overview:

The RLED2.97 range is a LED downlight, with fully adjustable gimbal and multi-faceted reflector.

### Range:

Powered by Tridonic SLE light engine.

Die-cast twist and lock bezel allows for a range of interchangeable accessories.

Dimming options.

Supplied with medium beam reflector as standard, with narrow and wide beam options available.

Two colour options: 3000K and 4000K

### Mounting:

Recessed - 102mm high, Weight 1.0kg

Ceiling depth - max. 35mm

Diameter - 186mm bezel

### Construction:

Steel fabrication / Cast Aluminium

### Controls:

Electronic switchDIM, DALI, DSI

- Standard

- ECO

### Efficiency:

Optical efficiency (DLOR)

93%

### Model Ref / Wattage / Luminaire Output / Colour temp

Model Ref	Wattage	Luminaire Output	Colour temp
RLED2.97.2010	5.1W	862lm	4000K
RLED2.97.2003	12.5W	1800lm	4000K
RLED2.97.2004	15.0W	2081lm	4000K
RLED2.97.3003	17.1W	2490lm	4000K
RLED2.97.3004	24.9W	3221lm	4000K
RLED2.97.5002	32.0W	4131lm	4000K
RLED2.97.2009	5.1W	797lm	3000K
RLED2.97.2001	12.5W	1720lm	3000K
RLED2.97.2002	17.1W	2140lm	3000K
RLED2.97.3001	17.1W	2374lm	3000K
RLED2.97.3002	24.9W	3071lm	3000K
RLED2.97.5001	32.0W	4028lm	3000K

