



Overview:

The RLED2.99 range is a fully adjustable LED scoop with Tridonic SLE module and a multi faceted reflector providing a wide flood beam.

Range:

Powered by Tridonic SLE light engine.
Supplied in white.
DALI dimming option.
Emergency option.
Two colour temps: 3000K & 4000K

Mounting:

Recessed - 165mm high, Weight 1.5kg
Ceiling depth - Max 35mm
Diameter - 186mm

Construction:

Steel fabrication / Cast Aluminium

Controls:

Electronic - Standard
DALI - DALI

Efficiency:

Optical efficiency (DLOR) 85%

Model Ref / Wattage / Luminaire Output / Colour temp

RLED2.99.2003	12.5W	1800lm	4000K
RLED2.99.2004	15.0W	2081lm	4000K
RLED2.99.3003	17.1W	2490lm	4000K
RLED2.99.4003	22.1W	3190lm	4000K
RLED2.99.3004	24.9W	3221lm	4000K
RLED2.99.4004	32.3W	4131lm	4000K
RLED2.99.2001	12.5W	1720lm	3000K
RLED2.99.2002	17.1W	2140lm	3000K
RLED2.99.3001	17.1W	2490lm	3000K
RLED2.99.4001	22.1W	3033lm	3000K
RLED2.99.3002	24.9W	3071lm	3000K
RLED2.99.4002	32.3W	4028lm	3000K