



Overview:

The RTMP range is a recessed trimmed LED luminaire manufactured from steel, with a RAL 9010 20% finish.

Range:

Powered by Tridonic light engines.

Provided with a micro prism high efficiency optic.

Modules available in two sizes, 600mm x 600mm or 1200mm x 300mm, both versions are 80mm deep.

Dimming options

Emergency options

Two colour temps: 3000K & 4000K

Mounting:

Recessed

Construction:

Steel fabrication

Controls:

Electronic	- ELE
DALI	- DALI
DSI	- DSI
Emergency 3hr	- EM
Emergency 3hr EMPRO	- EMP

Efficiency:

Optical efficiency (DLOR)	70%
---------------------------	-----

Model Ref / Wattage / Lumen package / Colour temp

RTMP.6.6.QG1.X.4K.350mA	37.6W	5280lm	4000K
RTMP.6.6.QG1.X.4K.500mA	56.2W	7280lm	4000K
RTMP.12.3.QG1.X.4K.350mA	37.6W	5280lm	4000K
RTMP.12.3.QG1.X.4K.500mA	56.2W	7280lm	4000K

* Above data quoted if for Tridonic QLE G1 LED light engines

** IP rating can be improved upon request

*** X denotes operating driver - ELE / DALI / DSI