



### Overview:

The SCLED range is a surface mounted decorative luminaire for use in mains and emergency. Available in three sizes. With aluminium spun body and injection moulded optic.

### Range:

Powered by LED light engines.  
Available in DALI.  
Semi recessing kit available.  
Integral emergencies can be supplied upon request.  
Three base colour options: White (WH), Brass (BR) and Chrome (CH).  
Two colour temps: 3000K & 4000K

### Mounting:

Surface

### Construction:

Aluminium  
Dimensions: 325mm Wide / 96mm Deep  
425mm Wide / 117mm Deep  
525mm Wide / 121mm Deep

### Controls:

Electronic - Standard  
DALI - DALI

### Efficiency:

Optical efficiency (DLOR)

### Model Ref / Wattage / Lumen package / Colour temp

SCLED.3.4000.8.6W	8.6W	1670lm	4000K
SCLED.3.4000.12.5W	12.5W	2300lm	4000K
SCLED.3.4000.21.9W	21.9W	3192lm	4000K
SCLED.4.4000.8.6W	8.6W	1670lm	4000K
SCLED.4.4000.12.5W	12.5W	2300lm	4000K
SCLED.4.4000.21.9W	21.9W	3192lm	4000K
SCLED.5.4000.8.6W	8.6W	1670lm	4000K
SCLED.5.4000.12.5W	12.5W	2300lm	4000K
SCLED.5.4000.21.9W	21.9W	3192lm	4000K