



### Overview:

The SL38DD dropped diffuser slotlight range is available in various lengths that can be connected to form a highly versatile system, corners and 'T' sections can be incorporated.

### Range:

The luminaire system can be used to create one continuous line of light, either surface mounted or wire suspended.

Infill sections are available in lengths and colours to suit your individual requirements.

Powered by Helvar or Harvard light engines.

Provided with a TPA rated high output satine optic, sealed to IP40.

Dimming option.

Emergency option.

Two colour temps: 3000K & 4000K

### Mounting:

Suspended (WS) - Provided with 2 metre suspension wires as standard.

Surface mounted (SM)

### Construction:

Extruded aluminium

### Controls:

Electronic	- ELEC
DSI	- DSI
DALI	- DALI

### Efficiency:

Optical efficiency (DLOR)	69%
---------------------------	-----

### Model Ref / Wattage / Lumen package / Colour temp

SL38DD.585.1.0B.840.X.OP	11.4W	1740lm	4000K
SL38DD.865.1.5B.840.X.OP	17.1W	2610lm	4000K
SL38DD.1145.2.0B.840.X.OP	22.8W	3480lm	4000K
SL38DD.1425.2.5B.840.X.OP	28.5W	4350lm	4000K
SL38DD.1705.3.0B.840.X.OP	34.2W	5220lm	4000K
SL38DD.1985.3.5B.840.X.OP	39.9W	6090lm	4000K
SL38DD.2265.4.0B.840.X.OP	45.6W	6960lm	4000K
SL38DD.2545.4.5B.840.X.OP	51.3W	7830lm	4000K
SL38DD.2825.5.0B.840.X.OP	57.0W	8700lm	4000K
SL38DD.3105.5.5B.840.X.OP	62.7W	9570lm	4000K
SL38DD.3385.6.0B.840.X.OP	68.4W	10440lm	4000K

X Denotes operating driver - ELEC / DSI / DALI

\* Above data quoted is for the Helvar LS-Series board, run at 250mA.

\*\* Shorter boards available upon request

\*\*\* IP rating can be improved upon request