

Overview:

The SL50-65DD dropped diffuser plaster in slotlight range is available in various lengths that can be connected to form a highly versatile system, corners and 'T' sections can be incorporated.

Range:

The luminaire system can be used to create one continuous line of light, either surface mounted or wire suspended.

Infill sections are available in lengths and colours to suit your individual requirements.

Powered by Tridonic or Harvard light engines.

Provided with a TPA rated high output satine optic, sealed to IP40.

Dimming option.

Emergency option.

Two colour temps: 3000K & 4000K

Two optic options: OP68 (Satine) & UG19 (UGR Optimised micro prism)

Mounting:

Plaster in

Construction:

Extruded aluminium

Controls:

Electronic	- ELEC
DSI	- DSI
DALI	- DALI

Efficiency:

Optical efficiency (DLOR)	73%
---------------------------	-----

Model Ref / Wattage / Lumen package / Colour temp

SL50-65DDP.585.1.0B.840.X.OP	8.0W	1340lm	4000K
SL50-65DDP.865.1.5B.840.X.OP	12.0W	2010lm	4000K
SL50-65DDP.1145.2.0B.840.X.OP	16.0W	2680lm	4000K
SL50-65DDP.1425.2.5B.840.X.OP	20.0W	3350lm	4000K
SL50-65DDP.1705.3.0B.840.X.OP	24.0W	4020lm	4000K
SL50-65DDP.1985.3.5B.840.X.OP	28.0W	4690lm	4000K
SL50-65DDP.2265.4.0B.840.X.OP	32.0W	5360lm	4000K
SL50-65DDP.2545.4.5B.840.X.OP	36.0W	6030lm	4000K
SL50-65DDP.2825.5.0B.840.X.OP	40.0W	6700lm	4000K
SL50-65DDP.3105.5.5B.840.X.OP	44.0W	7370lm	4000K
SL50-65DDP.3385.6.0B.840.X.OP	48.0W	8040lm	4000K

X Denotes operating driver - ELEC / DSI / DALI

* Above data quoted is for the Tridonic LLE Advanced board, run at 450mA.

** Shorter boards available upon request

*** IP rating can be improved upon request

