



### Overview:

The SL50 surface slotlight range is available in various lengths that can be connected to form a highly versatile system, corners and 'T' sections can be incorporated.

### Range:

The luminaire system can be used to create one continuous line of light.

Infill sections are available in lengths and colours to suit your individual requirements.

Powered by Tridonic or Harvard light engines.

Provided with a TPA rated high output satine optic, sealed to IP40.

Dimming option.

Emergency option.

Two colour temps: 3000K & 4000K

Two optic options: OP68 (Satine) & UGMP (UGR Optimised micro prism)

### Mounting:

Surface - Wall and ceiling mounted

### Construction:

Extruded aluminium

### Controls:

Electronic	- ELE
DSI	- DSI
DALI	- DALI

### Efficiency:

Optical efficiency (DLOR)	73%
---------------------------	-----

### Model Ref / Wattage / Lumen package / Colour temp

Model Ref	Wattage	Lumen package	Colour temp
SL50.580.1BH.840.X.OP68	10.5W	1660lm	4000K
SL50.860.1.5BH.840.X.OP68	15.7W	2490lm	4000K
SL50.1140.2BH.840.X.OP68	21.0W	3320lm	4000K
SL50.1420.2.5BH.840.X.OP68	26.2W	5810lm	4000K
SL50.1700.3BH.840.X.OP68	31.5W	4980lm	4000K
SL50.1980.3.5BH.840.X.OP68	36.7W	5810lm	4000K
SL50.2260.4BH.840.X.OP68	42.0W	6640lm	4000K
SL50.2540.4.5BH.840.X.OP68	47.2W	7470lm	4000K
SL50.2820.5BH.840.X.OP68	52.5W	8300lm	4000K
SL50.3110.5.5BH.2T.840.X.OP68	57.7W	9130lm	4000K
SL50.3390.6BH.2T.840.X.OP68	63.0W	9960lm	4000K

X Denotes operating driver - ELEC / DSI / DALI

\* Above data quoted is for the Tridonic LLE Advanced board, run at 450mA.

\*\* Shorter boards available upon request

\*\*\* IP rating can be improved upon request

**NEW UGR 19 OPTIC AVAILABLE FROM AUGUST 2016**

Data for 350mA and 400mA in 3000K and 4000K is available upon request. Wattages quoted do not include any losses from the driver