

## Overview:

The SLB range is available in various lengths that can be connected to form a highly versatile linear light bar system.

## Range:

The luminaire system can be used to create one continuous line of discreet light.

Powered by Helvar or Tridonic light engines.

Provided with a TPA rated high output satine optic, sealed to IP40.

Dimming option.

Two colour temps: 3000K & 4000K

## Mounting:

Surface (Other options available upon request)

## Construction:

Extruded aluminium

## Controls:

Electronic	- ELEC
DSI	- DSI
DALI	- DALI

## Efficiency:

Optical efficiency (DLOR)	85%
---------------------------	-----

## Model Ref / Wattage / Lumen package / Colour temp

SLB.570.1BH.840.X.OP	11.4W	1740lm	4000K
SLB.850.1.5BH.840.X.OP	17.1W	2610lm	4000K
SLB.1130.2BH.840.X.OP	22.8W	3480lm	4000K
SLB.1410.2.5BH.840.X.OP	28.5W	4350lm	4000K
SLB.1690.3BH.840.X.OP	34.2W	5220lm	4000K
SLB.1970.3.5BH.840.X.OP	39.9W	6090lm	4000K
SLB.2250.4BH.840.X.OP	45.6W	6960lm	4000K
SLB.2530.4.5BH.840.X.OP	51.3W	7830lm	4000K
SLB.2810.5BH.840.X.OP	57.0W	8700lm	4000K

X Denotes operating driver - ELEC / DSI / DALI

\* Above data quoted is for the Helvar LS-Series board, run at 250mA.

\*\* Shorter boards available upon request

\*\*\* IP rating can be improved upon request

Data for 350mA & 450mA in 3000K and 4000K available upon request.



