



Overview:

The SLED2.87 range is a circular LED surface mounted downlight, fitted with a satin etched reflector.

Range:

Powered by Philips DLM Flex light engine.
Finished in white, black, grey or a colour combination of those.
Dimming options.
Emergency options.
Two colour temps: 3000K & 4000K
Range of accessories to suit.

Mounting:

Surface - 240mm high, Weight 3.0kg

Construction:

Bezel die-cast aluminium

Controls:

Electronic	- Standard
touchDIM, DALI	- T+DALI
Emergency 3hr	- EM

Efficiency:

Optical efficiency (DLOR)	87%
---------------------------	-----

Model Ref / Wattage / Lumen package / Colour temp

Model Ref	Wattage	Lumen package	Colour temp
SLED2.87.1100.30	14.8W	1133lm	3000K
SLED2.87.2000.30	24.9W	1935lm	3000K
SLED2.87.3000.30	33.7W	2820lm	3000K
SLED2.87.5000.30*	48.5W	3966lm	3000K
SLED2.87.1100.40	14.9W	1237lm	4000K
SLED2.87.2000.40	24.9W	2117lm	4000K
SLED2.87.3000.40	33.7W	3078lm	4000K
SLED2.87.5000.40*	48.6W	4329lm	4000K

*Nuventix active cooling