



### Overview:

Square LED downlight with Tridonic DLE module fitted with a highly specular reflector and die cast bezel, with an option for a range of accessories.

### Range:

Tridonic light engine recessed downlight.  
Range of accessories available  
Dimming options  
Emergency options  
Two colour temps: 3000K & 4000K

### Mounting:

Recessed - 153mm high, weight 1.6kg  
Ceiling depth - Min. 5mm - Max. 40mm  
Square - 170mm x 170mm

### Construction:

Bezel die-cast from pure aluminium

### Controls:

Electronic	- Standard
SwitchDIM, DALI, DSI	- ECO
Emergency 3hr	- EM
Emergency 3hr self test	- EMS
Emergency 3hr EMPRO	- EMP

### Efficiency:

Optical efficiency (DLOR)	96%
---------------------------	-----

### Model Ref / Wattage / Luminaire Output / Colour temp

SQLED2.113.2003	9.9W	1182lm	4000K
SQLED2.113.2004	18.1W	2010lm	4000K
SQLED2.113.3003	17.5W	2049lm	4000K
SQLED2.113.3004	27.4W	3000lm	4000K
SQLED2.113.2001	9.9W	1084lm	3000K
SQLED2.113.2002	19.6W	1965lm	3000K
SQLED2.113.3001	17.4W	1879lm	3000K
SQLED2.113.3002	30.0W	2960lm	3000K