



Overview:

The SQLED2.122 range is a twin LED frame light with a Tridonic SLE light engine, fitted with a multi-faceted reflector providing excellent optical efficiency.

Range:

Tridonic SLE light engine recessed frame light.
Beam angle and interchangeable colour frames and bezels.
Two gimbal fixing positions for added flexibility.
Dimming options.
Two colour temps: 3000K & 4000K

Mounting:

Recessed - 145mm high, weight 3.4kg
Ceiling depth - max. 35mm
Square - 348mm x 189mm

Construction:

Bezel die-cast from pure aluminium

Controls:

Electronic	- Standard
touchDIM, DALI	- ECO
Emergency ILEM 3hr	- REM

Efficiency:

Optical efficiency (DLOR)	up to 93%
---------------------------	-----------

Model Ref / Wattage / Luminaire Output / Colour temp

SQLED2.122.2010/XY	10.2W	2 x 862lm	4000K
SQLED2.122.2003/XY	25.0W	2 x 1800lm	4000K
SQLED2.122.2004/XY	30.0W	2 x 2081lm	4000K
SQLED2.122.3003/XY	34.2W	2 x 2490lm	4000K
SQLED2.122.3004/XY	49.8W	2 x 3221lm	4000K
SQLED2.122.5002/XY	64.0W	2 x 4131lm	4000K
SQLED2.122.2009/XY	10.2W	2 x 797lm	3000K
SQLED2.122.2001/XY	25.0W	2 x 1720lm	3000K
SQLED2.122.2002/XY	34.2W	2 x 2140lm	3000K
SQLED2.122.3001/XY	34.2W	2 x 2374lm	3000K
SQLED2.122.3002/XY	49.8W	2 x 3071lm	3000K
SQLED2.122.5001/XY	64.0W	2 x 4028lm	3000K