



Overview:

The SQLED2.123 range is a triple LED frame light With a Tridonic SLE light engine, fitted with a multi-faceted reflector providing excellent optical efficiency.

Range:

Tridonic SLE light engine recessed frame light.
Beam angel and interchangeable colour frames and bezels.
Two gimbal fixing positions for added flexibility.
Dimming options.
Two colour temps: 3000K & 4000K

Mounting:

Recessed - 145mm high, Weight 4.5kg
Ceiling depth -max. 35mm
Square - 504mm x 189mm

Construction:

Bezel die-cast from pure aluminium

Controls:

Electronic - Standard
touchDIM, DALI - ECO
Emergency ILEM 3hr - REM

Efficiency:

Optical efficiency (DLOR) up to 93%

Model Ref / Wattage / Luminaire Output / Colour temp

Model Ref	Wattage	Luminaire Output	Colour temp
SQLED2.123.2010/XY	15.3W	3 x 862lm	4000K
SQLED2.123.2003/XY	37.5W	3 x 1800lm	4000K
SQLED2.123.2004/XY	45.0W	3 x 2081lm	4000K
SQLED2.123.3003/XY	51.3W	3 x 2490lm	4000K
SQLED2.123.3004/XY	74.7W	3 x 3221lm	4000K
SQLED2.123.5002/XY	96.0W	3 x 4131lm	4000K
SQLED2.123.2009/XY	15.3W	3 x 797lm	3000K
SQLED2.123.2001/XY	37.5W	3 x 1720lm	3000K
SQLED2.123.2002/XY	51.3W	3 x 2140lm	3000K
SQLED2.123.3001/XY	51.3W	3 x 2374lm	3000K
SQLED2.123.3002/XY	74.7W	3 x 3071lm	3000K
SQLED2.123.5001/XY	96.0W	3 x 4028lm	3000K